



# MYLES-1 MAGNETIC LINEAR ENCODER SYSTEM

# magnetic measuring scale and free floating unguided sensor head

- High resolution up to 0,001 mm resolution
- Sturdy metal case
- Best technology in small dimensions
- Shielded metal enclosure
- Easy mounting by gluing
- Contact-less and vear free system
- High resistance to vibrations to knocks
- Protection class IP67
- Resistant to humidity
- High accuracy
- Reliability reading transducer
- Measuring lengths of up to 100 m
- Connection cable up to 50 m
- Signal processing as standard with encoders





## **MYLES-1 Magnetic Linear Encoder System:**

The purpose of this sensor is to measure linear displacements on industrial machines & automation systems. The High precision Magnetic Linear Encoder System operates on an incremental principle. It consist of a sensing head and a magnetically encoded tape. Magnetic tapes are commonly made from a magnetic tape itself made from Strontium ferrite bonded into a plastic or rubber (elastomer) matrix which is then bonded onto a steel support. The sensing head glides over the tape, which is magnetized with alternating polarity, with a gap of up to 2,5 mm. Thus, since the system works on the principle of magnetism, unlike optical systems it is highly immune to contamination from oils, dust etc. The tape has alternating magnetic north/south poles are magnetized at a certain distance called the pole pitch. As the sensor is moved along the magnetic tape it detects the displacement and produces an output signal equivalent to that of an incremental encoder or a linear scale. Resolution is up to 1  $\mu$ m. Distance (gaps) of up to 2,5 mm (approx. 50 % of the pole width) above the magnetic tape are permitted. Also, accuracy classes of  $\pm 5 \,\mu$ m is achieved. These properties make it ideal for use in harsh, dusty industrial environments such as found in the wood industry.





#### Magnetic Scales, what do I need them for?

Beacuse, magnetic scales are attracting more and more interest even in areas and applications where "conventional" and expensive glass scales were predominant so far.

In today's life, many problems can be solved by introducing position or angle measurement using Magnetic scales has become easy, even if you need non standard products.

#### **Applications:**

The MYLES-1 Magnetic Linear Encoder Systems, the magnetic tape B5 are incremental systems without contact for linear measures. The capacity to measure distances longer than a meter (moreover up to 100 m), easy assembling, absence of parts that contact / rub, a waterproof transducer and a water-oil-dust-shaving resistant strip make this system suitable for a large number of applications, while taking position measurements of machinery within industries such as: machine tools, automatic-, wood-, marble-, glassworking, PVC cutting, lathes, milling, grinding, welding machinery, etc. The measuring transducer integrates in the same device, a sensor sensitive to a magnetic field, an electronic signal conversion circuit, and an output circuit. The sensor running on the magnetic tape produces a signal which, opportunely amplified and worked out, is changed into an incremental position signal for interfacing with displays, PLC, CNC, axes control, etc.



# **TECHNICAL SPECIFICATIONS:**

5 $\mu m$ , 10 $\mu m$ , 25 $\mu m$ and 62,5 $~\mu m$ or on request
Push-Pull or TLL RS 422 Line Driver
A, /A, B, /B, Z, /Z
Max. 40mA per channel
1030VDC ±%20 or 5VDC ±%5
See drawing
Aluminium
Up to 100m cable length on request
Up to 2.5mm ( Depend on pole pitch )
3 m/s
B5 nitrile rubber temperature magnetic tape
± 1 Increment
± 1 Increment
-25+85°
IP67

# **ELECTRICAL CONNECTIONS:**

Signal Name	Open cable end	Conn. D-sub, (9 pin) Pin
٨		1
A	TELLOW	
/B	WHITE	2
5V or 24V	RED	3
0 V	BLACK	4
/A	BLUE	5
В	GREEN	6
/Z	GRAY	7
Z	PINK	8
GROUND	SHIELD	9



Standart 'Z' Signal Every 5mm Z Reference / Index

Optional 'Z' Signal ONE Z REFERENCE SIGNAL (for example on the startpoint)

# **DIMENSIONS:**





# **B5 Magnetic Tape:**



- Easy splicing and assembling
- Resistant to moisture and many fluids
- Extensive ruggedness against dust etc.
- The highly rugged, flexible

The highly rugged, flexible plastic magnetic tape can be applied to a machine tool easily. With a special industrial adhesive layered strip, B5 Magnetic Tape can be attached to the overside of the profile system.

The magnetic material is magnetised in defined and even distances and works as a solid measure. The magnetic scale retains its firmness by means of a spring steel base.

The magnetic band is supplied with a non-magnetic stainless steel cover for physical protection; for its fixing an adhesive tape is premounted.

As shown beside, the B5 magnetic tape is composed by three layers:

- 1 A flexible magnetic tape made of plastic material
- 2 A magnetised steel tape used to create a shield against any external magnetic disturb. Although, it's glued to the upper plastic layer in order to supply the correct mechanical consistency to the magnetic tape.
- 3 The third part is the most rigid one and therefore is supplied separately due to transport and application needs. It must be stick to layer 1 by the user. The steel tape is magnetically neutral and employed to mechanically protect the magnetic tape.



**B5 Magnetic Tape** 

# **MAGNETIC TAPE SPECIFICATIONS:**

Environmental conditions	
Operating temperature	-40°C to +120°C
Storage temperature	-40°C to +120°C
Water Protection	CrNi 17 7 stainless steel carrier nitrile rubber high temperature magnetic tane
Mechanical properties	
Width	10 mm
Thickness	1,2 mm
Length	Up to 100 m
Number of tracks	1
Pole pitch	1 mm; 2 mm, 5 mm
Absolute pole patern possible	yes
Accuracy	±0,04mm/m up to 50m length
Linear expansion coefficient	(11 ±1 ) x 10-6 / K

## **MAGNETIC TAPE DIMENSIONS:**





# **ORDERING CODE:**



MYLES-1 Series

- $05 = 5 \,\mu m$  resolution
- PPL = Push Pull signal output and 24 VDC Power Supply
- 2 = A, B signal output
- 5M = 5 meter cable