

PNOZ X2.1C 24VAC/DC 2n/o

774305



Safety relay (standalone) Inputs: 1- / 2-channel wiring with detection of shorts across contacts Outputs: 2 N/O. Automatic/manual start. UB 24 V AC/DC, Width: 45 mm, depth: 80 mm, plug-in spring-loaded terminal Monitoring E-STOP, safety gates.

技术细节

批准:	CE;cULus 认证;TÜV;CCC
应用选项:	安全门监控;瞬时紧急停止监控;限位开关
操作模式:	单通道;自动复位;双通道;手动复位;触点间短路检测
产品标准:	EN 60947-5-1
标准:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
供电电压 (V):	24,0
电源类型:	AC/DC
终端型:	固定式
终端类型:	螺丝端子
瞬时安全触点数量:	2
停止类别:	0
在DC13处的最大电流I (6个循环/最小):	7.0 A
在AC1处的最大电流5:	5.0 A
宽度尺寸:	45.0 mm
高度尺寸:	87.0 mm
深度尺寸:	80.0 mm
总重:	195 g
净重:	190 g
以摄氏度一表示的环境温度:	-10 - 55 °C



THE SPIRIT OF SAFETY

可选的配件



774090

COVER P-93
